

# Starlink Performance (Gen 3) Kit

**Brand:** Starlink

**Product Code:** SLP-10

**Stock:** In Stock

**Weight:** 11.50lb

**Dimensions:** 24.00in x 15.60in x 1.60in



**Price:** \$2,995.00

## Short Description

The Starlink Performance Gen 3 is the most rugged, enterprise-grade satellite terminal in the Starlink lineup, designed for mission-critical deployment across demanding environments. Whether on land, at sea, or in mobile units, this kit delivers unmatched performance and resilience.

Note: Special order item, see details below.

## Description

This Performance kit features a separate Advanced Power Supply and a durable, powder-coated aluminum enclosure, ensuring resilience in remote areas and harsh environments on land and at sea, including extreme weather conditions, high-vibration settings, and during in-motion usage.

It includes an Advanced Power Supply (AC/DC, PoE output), a robust aluminum flat-panel dish, and supports third-party routers. Ideal for maritime, mobile, industrial, and remote applications. Backed by a 3-year warranty and designed for 10-year field life.

## High-Endurance Build

- 400+ Mbps download speeds; gigabit-ready hardware.
- IP69K (installed)/IP68 (unplugged) protection: dustproof, submersible, and able to

withstand high-pressure washdowns.

- Operational extremes: -40 °F to 140 °F, wind tolerance up to 170+ mph (survivable up to 280 kph).
- Built-in heater melts snow at 3.5 in/hr (85 mm/hr).

### **Future-Proof Performance**

- Delivers 400+ Mbps today, with gigabit speeds enabled via software—no new hardware necessary.
- 140° antenna field-of-view and phased-array beamforming ideal for motion/vibration.

### **Power & Mounting Flexibility**

- Includes Advanced Power Supply with AC/DC input, PoE output, rack-mountable, and DC-backup ready
- 25 m (82 ft) performance cable; supports third-party routers or Starlink Gen 3 router
- Compatible with flat, pipe, wedge, and marine mounts for fixed or in-motion setups

### **Durable Design & Warranty**

- Rugged aluminum pan-style dish, designed for 10-year field life with 3-year warranty

#### Specifications: Starlink Performance Antenna

**Package Weight:** 11.8 kg (26 lbs)

**Package Dimensions:** 686 x 454 x 121 mm (27.0 x 17.9 x 4.8 in)

**Antenna:** Electronic Phased Array

**Field of View:** 140°

**Orientation:** Software Assisted Manual Orienting

**Weight:** 5.2 kg (11.5 lb)

**Operating Temperature:** -40°C to 60°C (-40°F to 140°F)

**Wind Speed:** Survivable: 280 kph+ (174 mph+)

**Snow Melt Capability:** Up to 85mm / hour (3.5 in / hour)

**Power Consumption:** Average: 75 - 100 W

#### **Router Compatibility:**

- Starlink Gen3 Router
- Starlink Router Mini
- 3rd Party Routers

#### **Environmental Rating:**

- IP69K (with cables installed)
- IP68 (no cables installed)

**Operating Temperature:** -40°C to 60°C (-40°F to 140°F)

#### Specifications: Starlink Power Supply

**Product Dimensions:** 310 mm x 180 mm x 40 mm (12.2 in x 7.1 in x 1.6in)

**Weight:** 2.1 kg (4.6 lbs)

**Power Specifications:** 100-240VAC, 12V-56VDC

**Environmental Rating:** IP68 (with cables installed or plugged)

What's Included:

- (1) Starlink Performance Gen 3 antenna (24" × 15.6" × 1.6", 11.5 lb)
- (1) Advanced Power Supply (12.2" × 7.1" × 1.6", 4.6 lb)
- (1) Starlink Performance (PoE) Cable (25m / 82 ft)
- (1) Starlink Ethernet Cable (5m / 16.4 ft)
- (1) Starlink AC Power Cable (1.5m / 4.9 ft)
- (1) Starlink DC Power Cable (1.5m / 4.9 ft)
- (1) Mounting hardware
- (1) Setup Documentation

Special Order Terms:

- Delivery in 14-18 Calendar Days
- 50% Advance Payment Required

**Product Gallery**





